

Laboratory Glassware Dryer

SIMPLE. RELIABLE. EFFICIENT.

Model GD1021 Laboratory Glassware Dryer

The Model GD1021 Laboratory Glassware Dryer is a high capacity cabinet dryer specifically designed to dry laboratory glassware of all shapes and sizes as well as other items used in the laboratory environment. Adjustable shelves allow several loads of glassware to be dried at the same time.

Key features

- All stainless steel construction
- Steam or electric heat
- Automatic temperature regulation
- Fully insulated exterior to maintain high temperatures in dryer chamber and limit radiation loss outside the washer
- Timer control for adjustable drying time
- Non-proprietary parts



Model GD1021

Requirements

GD1021					
Dimensions	Chamber W x H x D inch (cm)			External W x H x D inch (cm)	
	30 x 52 x 26 (76 x 132 x 66)			36 x 80 x 32 (91 x 203 x 81)	
Electrical	Model	Volts	Phase	Hz	Amps
	Steam	110	1	60	15
	Electric	208	3	60	20
Steam	Model	FPT	PSI (kPa)		lbs. (kg)/hr
	Steam	1/2" minimum	30-50 (207-345)		100 (45)
	Electric	N/A	N/A		N/A
Condensate return line	All models 1/2" FPT				
Exhaust	Model	Dia. in (cm)		° F (° C)	SCFM (m³/m)
	All models	4 (10)		180 (82)	100 (2.8)



© SMC-Roe • October 2016, English, subject to change without notice

Standard features

- Steam or electric heat
- Automatic temperature regulation
- Timer control for adjustable drying times
- Fully insulated exterior

Construction

- All stainless steel construction
- Electrical assemblies designed for high temperature sanitary wash-down environment
- Dryer door double-walled stainless steel construction
- Temperature controlled up to 240 °F