



UTILITIES AND SERVICE REQUIREMENTS

- ELECTRICAL 3 PH, 60 HZ, 22 H.P. (16.41 KW) CONNECTED LOAD
- STEAM 2" (5.08 CM) FPT 30-80 PSI (206.84-551.58 KPA)
- CONDENSATE 900 LBS/HR (408.23 KG/HR) PEAK FLOW
- HOT WATER 700 LBS/HR (317.52 KG/HR) AVERAGE FLOW
- COLD WATER 1 1/2" (3.81 CM) FPT
- DRAIN #1 1" (2.54 CM) FPT 35 PSI (241.32 KPA)
- DRAIN #2 1" (2.54 CM) FPT 35 PSI (241.32 KPA)
- EXHAUST 35 GPM (132.49 LITERS/MIN) AVG. FLOW
- 120 GPM (454.25 LITERS/MIN) MAX. TEMPERATURE
- 2" (5.08 CM) FPT, 180 DEG F. (82.22 DEG C) MAX. TEMPERATURE
- 120 GPM (454.25 LITERS/MIN) FLOW
- 12" (30.48 CM) DIA, 600 SCFM (16.99 CUBIC METERS/MIN)
- 180 DEG F. (82.22 DEG C) SATURATED

NOTE: All drawings, descriptions, prints, specifications, etc. bearing this notice, together with the information, and ideas contained therein, are the sole and exclusive property of Schlyer Machine. Any disclosure or use thereof not authorized in writing by Schlyer Machine is unlawful and will be prosecuted to the full extent of the law.

DWG. BY: LBRKE
 APR. BR: _____
 SCALE: 1=24
 SHEET: ___ OF: ___

DATE: 7/29/05
 JOB NO: _____
 NEXT ASSEMBLY: _____

DRAWING TITLE:
 RW 6290PC3 LH PRIMATE CAPE WASHER
SCHLYER MACHINERY CO. PART NO: 6290PC3 LH
 200 LAKE ST. WILSON, NY 14172